

Quiet-FloBlowerAustralia

Unmatched performance. Proven reliability.

- Small compact foot print
- Works with any control
- Easy to install and service
- Certified by Energy Safe Victoria
- AMP Connector or Standard Wall Connector





## Quiet-Flo Blower For Australia

All models have compact designs which allow for constrained space installations. Additionally, the Quiet-Flo air intake is below the output so that the blower can be mounted against a wall without any concern for flow restrictions. The blower will work with any air or electronic control system and comes with a 4 Pin AMP Connector or Standard Wall Plug. Optional unionized connections and check valves are available.



SPECIFICATIONS	
Volts	230-240VAC / 50/60Hz
HP	1
AMPS	3.8A
Cord	4 Pin AMP Connector or Standard Wall Plug
OPTIONS	
42170 42172	C/V 1/4 LB C/V 3/32 LB
42225 42230	C/V 1/4 LB HOSE SPG C/V 3/32 LB HOSE SPG
42235 42240	C/V ½ LB x 1" slip C/V ½ LB x 1" slip
42175	1.5" Slip quick disconnect

## **Model Overview**

8142-0050	Blower Quiet Flow Spa 1.0Hp 2meter Cord Amp (Bulk)
8142+0050	Blower Quiet Flow Spa 1.0Hp 2meter Cord (Single)
8142-0060	Blower Quiet Flow Spa 1.0Hp Cord Aus Plug (Bulk)
8142+0060	Blower Quiet Flow Spa 1.0Hp Cord Aus Plu (Single)

## Measurements apply to all models







